

# HYDROMAX FR-E 68

Product code: 261301801

## Fire resistant hydraulic fluid

This product is a long life hydraulic fluid based on high flash point synthetic esters, providing good lubricating properties and long equipment life. It meets the requirements of ISO 6743/4, HFDU and ISO 15380 HEES. It can be applied as hydraulic fluid whenever operating close to a heat source. The products are highly biodegradable so small leakages will not cause contamination.

## Applications

It is suitable for hydraulic applications in:

- Hot rolling
- Continuous casting
- Ingots conveyors
- Metal casting
- Stamping, forging and sintering
- Heat treatments ovens
- Welding machines

No special care is required when handling this product. It is compatible with most of the common rubbers of the mineral oil operated circuits including NBR in good condition. Natural rubbers and polyurethane are not recommended.

## Changeover

When using this product in a circuit which had been operating with a mineral hydraulic oil, it is sufficient to proceed as follows:

- Drain the circuit and clean the tank, making sure that the inner wall is not painted
- Take off and clean the filters
- Load the tank with this product to the minimum level
- Run the circuit 1 or 2 hours under low pressure monitoring all movements
- Unload, and then set the filters, load again the tank with new Hydromax FR-E, and operate in normal conditions

# HYDROMAX FR-E 68

Product code: 261301801

## Typical Performance Data

| Property   | Test Method | Value             |
|--|-------------|-------------------|
| Appearance                                       | visual      | Clear liquid      |
| Viscosity @ 40 °C, mm <sup>2</sup> /s            | ASTM D445   | 68                |
| Viscosity @ 100 °C, mm <sup>2</sup> /s           | ASTM D445   | 12.3              |
| Viscosity Index                                  | ASTM D2270  | >180              |
| Density @ 20 °C, kg/m <sup>3</sup>               | ASTM D1298  | 935               |
| Flash point, °C                                  | ASTM D92    | >300              |
| Pour point, °C                                   | ASTM D97    | <-30              |
| N.N., mgKOH/g                                    | ASTM D974   | <1                |
| Demulsibility, ml oil/ml water/ml emulsion (min) | ASTM D1401  | max. 40/37/3 (30) |

All performance data on this Technical Data Sheet are indicative only and can vary during production.