

Performance[®] OG-XL #65

OPEN GEAR & WIRE ROPE GREASE

Product Code

267801501

Industrial Spraycans



GREASE

Open Gear & Wire Rope Grease

This product is a specially formulated grease for open gears, chains, cables and wire ropes. It contains a high amount of solid lubricants (graphite) which provide excellent anti wear properties under the most severe circumstances. Shock loads, lack of hydrodynamic lubrication can easily be handled.

Performance OG-XL can be used for open gears, wire ropes, chains, cables and slides. It has strong adhesive properties and is water resistant.

Benefits:

- Aerosol packed for convenience
- High anti wear and friction reducing properties
- Strong adhesive properties
- Water resistance
- High dropping point resulting in high temperatures (up to 170°C peak temperatures)
- Dry lubrication properties up to 450°C (Graphite)
- Free of heavy metals and bitumen



e 400ml

Typical Performance Data

Typical	Value
Appearance	Greasy
Colour	Black
Lubricant	Semi synthetic, Graphite
Base Oil viscosity @ 40 °C, cSt	3500
NLGI	0
4-ball wear test welding load, kg	>800
Working temperature °C	-10 - 150
Dry lubrication °C	450

How to use:

Shake Matrix Performance OG-XL well before use. Best temperature to apply the grease is 15-25°C. All typical data mentioned on this tech data sheet are after the evaporation of the solvent. This is when the product has the optimum performance.

All performance data on this Technical Data Sheet are indicative only and can vary during production.