

Performance[®] TFD #69

SEMI DRY LUBRICANT CONTAINING PTFE

Product Code
267801901
Industrial Spraycans



LUBRICANT

Semi Dry Lubricant Containing PTFE

This product is a waxy PTFE based lubricant. Performance TFD is designed for repetitive movement applications. Moving parts last longer, work harder and need less maintenance when coated with Performance TFD at a wide temperature range of -20 to 120°C and incidental peak temperatures of 150°C.

Performance TFD is suitable for use in coin mechanisms, door and window guides/runners, wood working tables, lock parts, saws and planes, rack slides, wood furniture drawers, wood table slides, packaging equipment.

Benefits:

- Aerosol packed for convenience
- Clean easy application
- Good adhesion to most substrates
- Low friction
- Durable abrasion resistant surface
- Thin film
- Room temperature cure
- Translucent coating
- Life long lubrication in many applications



e 400ml

Typical Performance Data

Typical	Value
Appearance	Translucent
Colour	White
Lubricant	PTFE

How to use:

Substrates to be coated should be clean and dry, free from contamination and residues such as dirt, grease or powder before applying Performance TFD. Light abrasion followed by a solvent wipe will improve adhesion.

All performance data on this Technical Data Sheet are indicative only and can vary during production.