

# Performance<sup>®</sup> ZINC SPRAY #72

ZINC PROTECTION COATING SPRAY

**Product Code**

267802301

Industrial Sprayscans



PAINT

## Zinc Protection Coating Spray

This product is a high quality zinc spray to treat galvanized and untreated steel. Performance Zinc Spray is used as a rust and corrosion protection on iron and steel surfaces.

Performance Zinc Spray can be used for repair of damaged galvanic surfaces, protection of exhaust systems and protection of welding seams. It prevents cathodic corrosion and is resistant to petrol, chemicals and weather influences.

### Benefits:

- Fast drying
- Good filling property
- Good primer for subsequent painting
- Outstanding cathodic corrosion prevention
- Resistant to petrol
- Chemicals and weather influences
- Spot-weldable
- Excellent adhesion
- Resists temperatures up to 350°C



e 400ml

## Typical Performance Data

Typical	Value
Base	Epoxy-Ester
Colour	Grey
VOC content, % w/w	54
Solid content, % w/w	46
Coverage, m <sub>2</sub>	1.25 to 1.75
Dust dry	10 to 15 min
Tack free	20 to 30 min
Hardened/Re-sprayable	>24h
Heat resistant	Up to 350°C

### How to use:

The surface should be clean, dry and free of grease and or oil. The aerosol should have room temperature. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeters.

All performance data on this Technical Data Sheet are indicative only and can vary during production.